



NON-ENAMELED BUFFER TANK

PARAMETERS

Model	...	BC 200K60	BC 200K67	BC 300K	BC 500K80	BC 500K85	BC 750K	BC 1000K
Volume range	...	200	200	300	500	500	750	1000
Energy efficiency class	...	B	B	B	B	B	B	B
Rated pressure	MPa	0.3	0.3	0.3	0.3	0.3	0.3	0.3
Standing loss	W	53	54	50	73	60	75	87
Gross weight	kg	60	52	64	117	121	171	196
Insulation type	...	Rigid foam	Rigid foam	Rigid foam	Rigid foam	Rigid foam	Rigid foam	Rigid foam

CONNECTIONS

1: Inlet / Outlet		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
4: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F	G1/2 F
5: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
7: Inlet / Outlet		G3/4 F	G3/4 F	G3/4 F	G1 1/4 F	G1 1/4 F	G1 1/4 F	G1 1/4 F

DIMENSIONS

A	mm	200	195	205	220	220	330	330
C	mm	855	675	835	980	980	880	1050
D	mm	600	670	670	800	850	1100	1100
F	mm	515	445	575	635	635	645	760
G	mm	75	85	85	80	105	125	125
H	mm	1450	1215	1605	1765	1765	1675	2020
K	mm	855	695	945	1045	1045	960	1190
L	mm	1180	945	1315	1460	1460	1270	1620